



SHOWN WITH NAMUR ACCESSORY DRIVE. IDENTICAL MOUNTING PATTERNS AND SHAFT DRIVE EXIST ON BOTH SIDES, NAMUR ACCESSORIES MAY BE MOVED TO OPPOSITE SIDE.

MOUNTING PATTERNS: F16 AND 6.50x2.00 RECT

SHAFT: 55MM FEMALE DOUBLE SQUARE, 1.87 INCHES DEEP (MEASURED FROM MOUNTING SURFACE), 2 INCH BORE THRU SHAFT

PORT SIZES AS ORDERED, 1/4 NPT STANDARD



REV.	DESCRIPTION	DATE	DRAWNBY
A	INITIAL	9-JUN-2014	JRH
B	CORRECTED FEMALE DRIVE DEPTH NOTE	06-Jan-2015	JRH

STATUS	APPROVAL
Released	JRH 06 Jan 15

Except as shown, Dimensions are inches and standard Tolerances are:

Fractional +/- N/A
 Angular +/- N/A
 1 Decimal +/- N/A
 2 Decimal +/- N/A
 3 Decimal +/- N/A

DESCRIPTION	REVISION
	B

DO NOT SCALE DRAWING
PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QTRCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QTRCO, INC. IS PROHIBITED.

MATERIALS AS SPECIFIED BY PRODUCT LINE STANDARDS AND ORDERED OPTIONS. WEIGHT SHOWN WITH HEAVIEST MATERIAL OPTIONS.

DWG. NO.	REVISION	SHEET	OF	SIZE
Qx212DA-DIM-01	B	1	1	A
WEIGHT (Pounds): 87.27		1 of 1 if not shown		