



SHOWN WITH NAMUR ACCESSORY DRIVE. IDENTICAL MOUNTING PATTERNS AND SHAFT DRIVE EXIST ON BOTH SIDES, NAMUR ACCESSORIES MAY BE MOVED TO OPPOSITE SIDE.

MOUNTING PATTERNS: F16 AND 6.50x2.00 RECT

SHAFT: 55MM FEMALE DOUBLE SQUARE, 1.87 INCHES DEEP (MEASURED FROM MOUNTING SURFACE), 2 INCH BORE THRU SHAFT

PORT SIZES AS ORDERED, 1/4 NPT STANDARD



DETAIL A
SCALE 2 : 7

REV.	DESCRIPTION	DATE	DRAWNBY
A	INITIAL	9-JUN-2014	JRH
B	CORRECTED FEMALE DRIVE DEPTH NOTE	06-Jan-2015	JRH

STATUS	APPROVAL
Released	JRH 06 Jan 15

Except as shown, Dimensions are inches and standard Tolerances are:

Fractional +/- N/A
 Angular +/- N/A
 1 Decimal +/- N/A
 2 Decimal +/- N/A
 3 Decimal +/- N/A

DESCRIPTION

DO NOT SCALE DRAWING
PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QTRCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QTRCO, INC. IS PROHIBITED.

MATERIALS AS SPECIFIED BY PRODUCT LINE STANDARDS AND ORDERED OPTIONS. WEIGHT SHOWN WITH HEAVISET MATERIAL OPTIONS.

DWG. NO.	REVISION
Qx212SR-DIM-01	B
WEIGHT (Pounds): 112.80	SHEET 1 OF 1 1 of 1 if not shown
SIZE A	