



SHOWN WITH NAMUR ACCESSORY DRIVE. IDENTICAL MOUNTING PATTERNS AND SHAFT DRIVE EXIST ON BOTH SIDES, NAMUR ACCESSORIES MAY BE MOVED TO OPPOSITE SIDE.

MOUNTING PATTERNS: F16 AND 6.50x2.00 RECT

SHAFT: 55MM FEMALE DOUBLE SQUARE, 1.87 INCHES DEEP (MEASURED FROM MOUNTING SURFACE), 2 INCH BORE THRU SHAFT

PORT SIZES AS ORDERED, 1/4 NPT STANDARD

CoG MEASUREMENTS SHOWN WITH 16-INCH HANDWHEEL IN EXTENDED POSITION

SHOWN WITH 16-INCH DIAMETER ELEVATED HANDWHEEL. ACTUAL SIZE MAY VARY AS ORDERED.



REV.	DESCRIPTION	DATE	DRAWNBY
A	INITIAL	19-JAN-2015	JRH

STATUS	APPROVAL
Released	JRH 19 Jan 15

Except as shown, Dimensions are inches and standard Tolerances are:  
 Fractional +/- N/A  
 Angular +/- N/A  
 1 Decimal +/- N/A  
 2 Decimal +/- N/A  
 3 Decimal +/- N/A

DESCRIPTION

DO NOT SCALE DRAWING  
**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QTRCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QTRCO, INC. IS PROHIBITED.

MATERIALS AS SPECIFIED BY PRODUCT LINE STANDARDS AND ORDERED OPTIONS. WEIGHT SHOWN WITH HEAVIEST MATERIAL OPTIONS.

DWG. NO.	REVISION
<b>Qx212SR-JR-DIM-01</b>	A
WEIGHT (Pounds): 133.17	SHEET 1 OF 1 1 of 1 if not shown